

2AMW52U4RXC

| Combinazioni unità interne | RAFFREDDAMENTO | | | | | | | | | | | | | | |
|----------------------------|---------------------|------|------|------|------|------------------|-----|------|------|-----|------|--------|------|--------|-----|
| | Capacità totale (W) | | | | | Assorbimento (W) | | | | EER | (A) | Pdc(W) | SEER | Classe | Qce |
| | A | B | NOM | MIN | MAX | NOM | MIN | MAX | W/W | | | | | | |
| 1.5+2.5 | 1500 | 2500 | 4000 | 1200 | 5000 | 1000 | 390 | 2000 | 4,00 | 4,4 | 4000 | 7,40 | A++ | 189 | |
| 1.5+3.5 | 1500 | 3500 | 5000 | 1200 | 6600 | 1260 | 390 | 2500 | 4,00 | 5,5 | 5000 | 7,60 | A++ | 230 | |
| 2.0+2.0 | 2000 | 2000 | 4000 | 1200 | 5000 | 1000 | 390 | 2000 | 4,00 | 4,4 | 4000 | 7,40 | A++ | 189 | |
| 2.0+2.5 | 2000 | 2500 | 4500 | 1200 | 6000 | 1150 | 390 | 2300 | 3,91 | 5,1 | 4500 | 7,50 | A++ | 210 | |
| 2.0+3.5 | 2000 | 3000 | 5000 | 1200 | 6600 | 1260 | 390 | 2500 | 3,97 | 5,5 | 5000 | 7,50 | A++ | 233 | |
| 2.5+2.5 | 2500 | 2500 | 5000 | 1200 | 6600 | 1245 | 390 | 2500 | 4,02 | 5,5 | 5000 | 7,60 | A++ | 230 | |
| 2.5+3.5 | 2300 | 2700 | 5000 | 1200 | 6600 | 1245 | 390 | 2500 | 4,02 | 5,5 | 5000 | 7,65 | A++ | 229 | |
| 3.5+3.5 | 2500 | 2500 | 5000 | 1200 | 6600 | 1245 | 390 | 2500 | 4,02 | 5,5 | 5000 | 7,65 | A++ | 229 | |

| Combinazioni unità interne | RISCALDAMENTO | | | | | | | | | | | | | | |
|----------------------------|---------------------|------|------|------|------|------------------|-----|------|------|-----|------|--------|------|--------|-----|
| | Capacità totale (W) | | | | | Assorbimento (W) | | | | COP | (A) | Pdh(W) | SCOP | Classe | Qhe |
| | A | B | NOM | MIN | MAX | NOM | MIN | MAX | W/W | | | | | | |
| 1.5+2.5 | 1800 | 2800 | 4600 | 1200 | 6500 | 1200 | 290 | 2000 | 3,83 | 5,3 | 4000 | 4,10 | A+ | 1366 | |
| 1.5+3.5 | 1800 | 3200 | 5000 | 1200 | 7000 | 1300 | 290 | 2300 | 3,85 | 5,7 | 4500 | 4,30 | A+ | 1465 | |
| 2.0+2.0 | 2300 | 2300 | 4600 | 1200 | 6500 | 1200 | 290 | 2000 | 3,83 | 5,3 | 4000 | 4,10 | A+ | 1366 | |
| 2.0+2.5 | 2300 | 2700 | 5000 | 1200 | 6700 | 1300 | 290 | 2300 | 3,85 | 5,7 | 4500 | 4,30 | A+ | 1465 | |
| 2.0+3.5 | 2000 | 3500 | 5500 | 1200 | 7000 | 1300 | 290 | 2500 | 4,23 | 5,7 | 4500 | 4,30 | A+ | 1465 | |
| 2.5+2.5 | 2750 | 2750 | 5500 | 1200 | 7000 | 1300 | 290 | 2500 | 4,23 | 5,7 | 4500 | 4,40 | A+ | 1432 | |
| 2.5+3.5 | 2500 | 3000 | 5500 | 1200 | 7000 | 1290 | 290 | 2500 | 4,26 | 5,7 | 4500 | 4,60 | A++ | 1370 | |
| 3.5+3.5 | 2750 | 2750 | 5500 | 1200 | 7000 | 1280 | 290 | 2500 | 4,30 | 5,6 | 4500 | 4,62 | A++ | 1364 | |

